



PART LIST

							ŧ
26"Closet frame	26"Closet side board	52"Wooden work plate	26"Skirting board	26"Cabinet frame	flange screw (M6X25)	Hexagon bolt with	Description
47288	47389	47279	47289	47280			Part#
1 pc	1 pc	1 pc	2 pcs	1 pc		8 pcs	QTY


. ----.





1.INSTALL ADJUSTABLE SHELF


Decide the height of the adjustable shelf onto the tongues on both side panels. Insert the bolts into the side panels.Place the shelf on the bolts. Make sure slot B go into box first.



ASSEMBLY INSTRUCTIONS


2.ADJUST LEVELER

Adjust the levelers and make the whole unit to stable state.




3. PRE-DRILL HOLES OF WOODEN WORK PLATE

Pre-drill eight small holes under the wooden work plate for easily installing.



4.INSTALL WOODEN WORK PLATE

Position the wooden work plate on the top of cabinets. Remove the top drawer of cabinet and open the 2-door cabinet . Insert the Hexagon bolt with flange screw(M6X25) through the top of cabinet, and into the bottom of the wooden worktop. Tighten securely. Reinstall the drawers.



5.INTALL SKIRTING BOARDS

Position the skirting boards on the legs of cabinets. Insert the truss head screw (M6X12, stainless) through the legs. Tighten securely. Repeat the steps for other skirting boards.

